

Figures

Chapter 1 – Overview of a Ship's Electrical System
Figure 1.1 – The Marine Environment
Figure 1.2 – Degrees of Freedom of a Ship at Sea
Figure 1.3 – A Modern Ship's Typical Electrical System
Figure 1.4 – Dimensioning the Electrical Network
Figure 1.5 – Block Diagram of a Ship's Electrical System
Figure 1.6 – A Typical Electrical System Diagram
Figure 1.7 – Circuit Diagram of a Direct-on-Line Motor Starter With Local, Remote and Automatic Options
Figure 1.8 – Wiring Diagram of the Motor Starter in Figure 1.6
Chapter 2 – Electrical Safety
Figure 2.1 – Common Circuit Faults
Figure 2.2 – Current Paths in General
Figure 2.3 – Nameplate for Equipment used in Hazardous Areas
Figure 2.4 – Flameproof (Explosion proof) Enclosures
Figure 2.5 – Pressurised Apparatus with Leakage Compensation - Enclosure without Rotating Parts
Figure 2.6 – Pressurised Apparatus with Leakage Compensation - Rotating Electrical Machine with Internal fan
Figure 2.7 – Pressurised Apparatus with Leakage Compensation - Rotating Electrical Machine with External Fan
Figure 2.8 – An Intrinsically-safe Circuit
Figure 2.9 – General Tanker Arrangement showing Hazardous Areas
Chapter 3 – Distribution Systems
Figure 3.1 – Single-Phase Two Wire Systems
Figure 3.2 – Single-Phase Three-Wire System
Figure 3.3 – Three-Phase Three Wire System – Delta Connected
Figure 3.4 – Three-Phase Three Wire System – Star Connected
Figure 3.5 – Three-Phase Four Wire System – Star Connected
Figure 3.6 – 8-Nodes Star Network
Figure 3.7 – Bus bar – type Network
Figure 3.8 – Cross-linked-type (Unconstrained) Network

Figures

Chapter 4 – Emergency Power and Shore Supply
Figure 4.1 – An Emergency Generator
Figure 4.2 – Emergency Power Supply System
Figure 4.3(a) – Emergency Generator's Manual and Automatic Flow Chart
Figure 4.3(b) – Emergency Generator's Routine Testing Flow Chart
Figure 4.4 – Shore Supply Arrangement

Chapter 5 – Insulated and Earthed Neutral Systems
Figure 5.1 – Insulated Neutral System
Figure 5.2 – Earthed Neutral System
Figure 5.3 – Significance of Earth Faults in an Earthed Distribution System
Figure 5.4 – Single Earth Fault in an Insulated Distribution System
Figure 5.5 – Double Earth Fault in an Insulated Distribution System
Figure 5.6 – High Voltage System Earthing
Figure 5.7 – Earth Fault Indicators
Figure 5.8 – Earth Fault Instrument
Figure 5.9 – Monitoring of Earth Fault Current in a 3-phase Motor
Figure 5.10 – Direct Measurement of AC Leakage at the Neutral
Figure 5.11 – Three-phase Insulation Monitor
Figure 5.12 – Detection and Clearance of an Earth Fault – The First Step
Figure 5.13 – Detection and Clearance of an Earth Fault – The Second Step

Chapter 6 – Alternators
Figure 6.1 – Fleming's Right Hand Rule
Figure 6.2 – The Elementary Alternator
Figure 6.3 – The Elementary Generator's Sine Wave Output (Rotating Armature)
Figure 6.4 – A Simple Rotating Field Alternator
Figure 6.5 – Stator Construction
Figure 6.6 – Cross-section of a Stator Slot and Winding
Figure 6.7 – Bar-type Conductors
Figure 6.8 – EMF Generation in a Rotating Field Alternator

Figures

Chapter 6 – Alternators (Continued)
Figure 6.9 – A Cylindrical or Turbo Alternator
Figure 6.10 – High Speed Salient Pole Rotor
Figure 6.11 – Slow Speed Salient Pole Rotor
Figure 6.12 – Conventional Shaft Generator System
Figure 6.13 – Shaft Generator with a Static Frequency Converter
Figure 6.14 – Large Slow-speed Main Engine with an Alternator at the Non-driving End
Figure 6.15 – Generator Drive from the Intermediate Shaft
Figure 6.16 – Generator Driven by Power Take-off from the Main Engine
Figure 6.17 – Shaft Generator Supplying a High-voltage System for a Dredger
Figure 6.18 – Three Phase Rectifier and its Associated Wave-forms
Figure 6.19 – Power Factor Correction (Phasor Diagram) Using a Synchronous Motor
Figure 6.20 – Phasor Diagram for an Unloaded Synchronous Motor
Figure 6.21 – Generator Starting and ACB Closure onto a Dead Bus Bar (for a Diesel Generator)
Figure 6.22 – Exhaust gas Turbo-generator System
Figure 6.23 – An Electrically Coupled System
Figure 6.24 – The Brushless Alternator's Circuit Diagram and Sectional View
Figure 6.25 – Brushless Alternator – Construction

Chapter 7 – Direct Current Generators
Figure 7.1 – The DC Armature, Commutator and Brush Assembly
Figure 7.2 – DC Machine Construction
Figure 7.3 – A Four-pole Generator
Figure 7.4 – Armature and Commutator in a Two-Pole Machine
Figure 7.5 – The Commutator's Role
Figure 7.6 – Flux Distribution in a DC Generator
Figure 7.7 – Reduced Pole Tip Area
Figure 7.8 – Compensating Windings
Figure 7.9 – Interpole Principles
Figure 7.10 – Commutation in a DC Generator
Figure 7.11 – Series Wound Generator

Figures

Chapter 7 – Direct Current Generators (Continued)
Figure 7.12 – Shunt Wound Generator
Figure 7.13 – Shunt Generator External Characteristics
Figure 7.14 – Compound Wound Generator
Figure 7.15 – Compound Wound Generator – Long Shunt Type
Figure 7.16 – Field Winding Terminal Markings
Figure 7.17 – Compound Generator’s External Characteristics
Figure 7.18 – Compounding Adjustment with the Diverter
Figure 7.19 – Series Resistance Control of Shunt and Compound Wound DC Generators
Figure 7.20 – Hand–operated Shunt–field Rheostat

Chapter 8 – Automatic Voltage Regulators
Figure 8.1 – Self–excitation System
Figure 8.2 – PMG–excited AVR Controlled Generator
Figure 8.3 (a) – Static Automatic Voltage Regulator
Figure 8.3(b) – Characteristic of a Zener Diode
Figure 8.4(a) – A Thyristor–controlled Static Excitation System
Figure 8.4(b) – Role of the Thyristor
Figure 8.4(c) – An Alternative Circuit of a Thyristor–controlled Static Excitation System
Figure 8.5 – Transformer–based Static Excitation System
Figure 8.6 – Typical Voltage Dip / Recovery Pattern for an Alternator
Figure 8.7 – Comparison of Voltage Dip / Recovery Pattern for Different Excitation Systems
Figure 8.8 – Variation of Excitation at Constant Voltage
Figure 8.9 – Variation of Voltage at Constant Excitation
Figure 8.10 – Exertion of Torque on the Rotor due to the Stator Field
Figure 8.11 – Governor Characteristic
Figure 8.12 – Opposition of the Stator & Rotor Fields
Figure 8.13 – Typical Direct–feed Thyristor AVR
Figure 8.14 – Static Excitation AVR Circuit
Figure 8.15 – The UFRO control potentiometer sets the knee point.
Figure 8.16 – Dip Function Potentiometer Adjustment

Figures

Chapter 8 – Automatic Voltage Regulators (Continued)
Figure 8.17 – Dwell Function
Figure 8.18 – Effect of Droop in a Two-generator System
Figure 8.19 – Block Diagram of a Modern AVR
Chapter 9 – Panel Instrumentation
Figure 9.1 – A Moving Coil in a Magnetic Field (No Current Flow)
Figure 9.2 – A Moving Coil in a Magnetic Field (Current Flowing)
Figure 9.3 – Basic Arrangement in a PMMC Meter
Figure 9.4 – D'Arsonval Movement in a PMMC Meter
Figure 9.5 – Power Measurement in DC Circuits (Variant 1)
Figure 9.6 (a)– Power Measurement in DC Circuits (Variant 2)
Figure 9.6(b) – The Magic Circle
Figure 9.7 – Power Measurement using Instrument Transformers
Figure 9.8 – The Basic Electrodynamicometer
Figure 9.9 – Circuit of an Electrodynamicometer Wattmeter
Figure 9.10 – Variation of Mutual Induction with Deflection
Figure 9.11 – Power in Poly-phase Systems
Figure 9.12 – Three Wattmeter Method in a 3-Phase – 4-Wire Circuit
Figure 9.13 – Two Wattmeter Method – Star Connection
Figure 9.14 – Two Wattmeter Method – Delta Connection
Figure 9.15 – Phasor Diagram for a Star-connected Load
Figure 9.16 – One Wattmeter Method
Figure 9.17 – Phasor Diagram – One Wattmeter Method
Figure 9.18 – Three-phase Two Element Wattmeter
Figure 9.19 – Single Phase Reactive Power Meter
Figure 9.20 – Phasor Diagram
Figure 9.21 – Reactive Power Measurement (3-Phase) with Two Autotransformers
Figure 9.22 – Phasor Diagram – 3-Phase Reactive Power Measurement
Figure 9.23 – Reactive Power Measurement with One Wattmeter
Figure 9.24 – Phasor Diagram for Figure 9.23

Figures

Chapter 9 – Panel Instrumentation (Continued)
Figure 9.25 – Single-phase Electrodynamicometer Power Factor Meter
Figure 9.26 – Phasor Diagram
Figure 9.27 – A Three-phase Electrodynamicometer-type Power Factor Meter
Figure 9.28 – Phasor Diagram for Figure 9.27
Figure 9.29 – Three-Phase Moving Iron Power Factor Meter
Figure 9.30 – Phasor Diagram for Figure 9.29
Figure 9.31 – Vibrating Reed Frequency Meter
Figure 9.32 – Frequency versus Amplitude
Figure 9.33 – Indications from Vibrating Reeds
Figure 9.34 – Electrodynamicometer-type Frequency Meter
Figure 9.35 – Simple Weston-type Synchroscope
Figure 9.36 – An Improved Version of the Weston Synchroscope
Figure 9.37 – Phasor Diagrams for Different Conditions of the Bus bar and Incoming Voltages
Figure 9.38 – Dial of a Weston Synchroscope
Figure 9.39 – Alternative Arrangement (Circuit) in a Synchroscope
Figure 9.40 – Dial of a Rotating-type Phase Sequence Indicator
Figure 9.41 – Static-type Phase Sequence Indicator
Figure 9.42 – The DC Tachometer
Figure 9.43 – The Drag Cup Tachometer (AC)
Chapter 10 – Paralleling of Alternators
Figure 10.1(a) – The Four Basic Stages of Synchronising.
Figure 10.1(b) – Diesel – driven Alternator Starting and Synchronising
Figure 10.2 – Auto Synchronising Unit
Figure 10.3(a) – Diesel–Driven Alternator Starting and Synchronising
Figure 10.3(b) – Diesel–Driven Alternator Starting and Synchronising (Automatic Operation)
Figure 10.4 – Arrangement of Synchronising Lamps
Figure 10.5 – Phasor Rotation while Synchronising
Figure 10.6 – Synchronising Instruments
Figure 10.7 – Excitation Control Phasors

Figures

Chapter 10 – Paralleling of Alternators (Continued)
Figure 10.8 – Throttle Control Phasor
Figure 10.9 – Throttle Control Phasor
Figure 10.10 – Throttle Control Phasor
Figure 10.11 – Shifting of Speed-load Characteristic
Figure 10.12 – Load sharing of two alternators
Figure 10.12(a) – Load Sharing Characteristics Plotted Back-to-Back
Figure 10.13 – Load Sharing (Back to Back)
Figure 10.14 – kVAr Load Sharing (Plot Not To Scale)
Figure 10.15 – Torque-speed Characteristic of an Induction Machine
Figure 10.16 – The Terminal Voltage-current Characteristic of an Induction Generator for a load with a constant lagging power factor
Chapter 11 – Switchboards and Switchgear
Figure 11.1 – Typical Layout of a Main Switchboard
Figure 11.2(a) – A Main Switchboard in the Machinery Control Room
Figure 11.2(b) – Close-up View of a Main Switchboard
Figure 11.2(c) – A Modern Main Switchboard
Figure 11.3 – Bus bars in a Switchboard
Figure 11.4 – A Synchronising Panel
Figure 11.5 – A Generator Control Panel
Figure 11.6(a) – Sectional View of an Air Circuit Breaker
Figure 11.6(b) – Pictorial Diagram of an Air Circuit Breaker
Figure 11.7 – Air-break Circuit Breaker (ACB) for Alternators
Figure 11.8(a) – Moulded Case Circuit Breakers
Figure 11.8(b) – Sectional View of a Moulded Case Circuit Breaker
Figure 11.9 – A Miniature Circuit Breaker (MCB) operating during a Short-circuit
Figure 11.10 – Residual Current Circuit Breakers – 4-Pole and 2-Pole

Figures

Chapter 12 – Starters for Miscellaneous Equipment
Figure 12.1 – Breakaway Starting Current of Standard Motors As a Multiple of Rated Operational Current
Figure 12.2 – Typical Starting Current Curve (as a Multiple of Rated Operating Current) As a Factor of Rotational Speed of Squirrel Cage Motors
Figure 12.3 – Standard Values for Run-up Times of Standard Motors As a Function of Rated Power
Figure 12.4 – Power and Control Circuits of a Direct-on-line Starter
Figure 12.5 – Remote Control Circuit for a Direct-on-line Starter
Figure 12.6 – A Direct-on-line Starter's Circuit for a Pump
Figure 12.7 – An Engine Room Crane's D.O.L. Power Circuit
Figure 12.8 – Control Circuit for the Engine Room Crane
Figure 12.9 – Star Connections for Speed Variation
Figure 12.10 – Delta Connections for Speed Variation
Figure 12.11 – Variation of Current with Speed in Star and Delta-connected Windings
Figure 12.12 – Variation of Torque with Speed in Star and Delta-connected Windings
Figure 12.13 – A Basic Star – Delta Starter
Figure 12.14 – Switch-over Pause too short – Short-circuit across the Arc - The Fuse is tripped and the System is turned off
Figure 12.15 – Switch-over Pause too long – Shaft Speed drops off
Figure 12.16 – Correct Wiring of Motor Phases for Clock-wise Rotation
Figure 12.17 – Incorrect Wiring of Motor Phases – also causes Clock-wise Rotation
Figure 12.18 – Correct Wiring of Phases for Counter-clockwise Rotation
Figure 12.19(a) – Star-Delta Starter with Fusible Isolator (Power Circuit)
Figure 12.19(b) – Control Circuit – Star-Delta Starter with Fusible Isolator
Figure 12.20 – Star-delta Starter for a Seawater Pump
Figure 12.21(a) – Comparison of Direct-on-line and Star-Delta Characteristics (Torque versus Speed)
Figure 12.21(b) – Comparison of Direct-on-line and Star-Delta Characteristics (Current versus Speed)
Figure 12.22(a) – Comparison of Motor Starting Characteristics (Torque versus Slip)
Figure 12.22(b) – Comparison of Motor Starting Characteristics (Current versus Slip)
Figure 12.23 – Autotransformer Starter
Figure 12.24 – Starter Panel for a Slip Ring Induction Motor
Figure 12.25 – Basic Diagram for Electronic Starter Utilizing Six Thyristors
Figure 12.26 – Basic Diagram for Electronic Starter Utilizing Three Thyristors and Three Diodes

Figures

Chapter 12 – Starters for Miscellaneous Equipment (Continued)
Figure 12.27 – Effect of Ramp Time on Speed–Torque Characteristics of a Soft Starter
Figure 12.28 – Typical Torque–Speed Characteristics for an Electronic Starter
Figure 12.29 – Timed Voltage Ramp
Chapter 13 – Fault Protection Devices
Figure 13.1 – Protection Features of a Typical Marine Electrical System (AC)
Figure 13.2 – Instantaneous Short–circuit Trip Mechanism (DC)
Figure 13.3 – Overload Trip (DC)
Figure 13.4(a) – Overload and Preferential Trips (Circuit)
Figure 13.4(b) – Overload and Preferential Trips (Flow Chart)
Figure 13.5 – Reverse Current Trip Mechanism (DC)
Figure 13.6 – Under–voltage Release Mechanism (DC)
Figure 13.7 – Overload Relay – (Inverse Definite Minimum Time Relay)
Figure 13.8 – Resultant Inverse Time Characteristics of the IDMT Relay
Figure 13.9 – Reverse Power Relay
Figure 13.10 – Cartridge Fuses
Figure 13.11 – Enclosed Fuse
Figure 13.12 – Diazed (Bottle) Fuses
Figure 13.13 – Neozed Fuses
Figure 13.14 – NH Fuses
Figure 13.15 – A High Rupturing Capacity Fuse
Figure 13.16 – Inverse Time–Current Curve for a 30A HRC Fuse (Not to Scale)
Figure 13.17 – Screw Caps
Figure 13.18 – Protection Discrimination
Figure 13.19 – Tripping Characteristic of Back–up Fuses (Crosses the OCR Characteristic at the Motor’s Starting Current Value)
Figure 13.20 – Open Circuit Fault in a Motor’s Supply Circuit
Figure 13.21 – Full–load Healthy Condition
Figure 13.22 – Half–load Single–phase Condition
Figure 13.23 – Principle of Operation of a Thermal OCR on Overload
Figure 13.24 – Differential Devices for Thermal Overload

Figures

Chapter 13 – Fault Protection Devices
Figure 13.25(a) – PTC Thermistor Curve (Resistance versus Temperature)
Figure 13.25(b) – Typical Circuit Involving Thermistors for Protection
Figure 13.25(c) – Physical Specifications

Chapter 14 – Electric Cables
Figure 14.1 – Cable Cores
Figure 14.2 – Cable Testing

Chapter 15 – Cable Insulation and Ingress Protection
Figure 15.1 – Temperature versus Life Span
Figure 15.2 – Chain Formation by Bi-functional Molecules
Figure 15.3 – Branched Chain Polymer
Figure 15.4 – Formation of a Three-dimensional Giant Molecule
Figure 15.5 – Cable Glands
Figure 15.6 – Cable Terminals

Chapter 16 – Transformers
Figure 16.1 – Basic Operation of a Transformer
Figure 16.2 – Hollow Laminated Core of a Transformer
Figure 16.3 – Hollow Laminated Core of a Transformer with Windings
Figure 16.4 – Shell-type Core Construction
Figure 16.5 – Exploded View of a Shell-type Transformer
Figure 16.6 – Step-down Transformer
Figure 16.7 – The Dot Convention
Figure 16.8 – No-load Condition of a Transformer
Figure 16.9(a) – Three-phase Lighting Transformer – 3-Wire $\Delta - \Delta$ Connection
Figure 16.9(b) – Simplified Circuit of the 3-Wire $\Delta - \Delta$ Connection
Figure 16.10(a) – $\Delta - \Delta$ Transformers with one Unit Disconnected
Figure 16.10(b) – Simplified Circuit – $\Delta - \Delta$ Transformers with one Unit Disconnected
Figure 16.11 – Three-phase Lighting Transformer – Delta-Star Connection

Figures

Chapter 16 – Transformers
Figure 16.12 – The Fixed Ratio Auto-transformer
Figure 16.13 – The Variable Ratio Auto-transformer
Figure 16.14 (a) – Pictorial Views of Instrument Transformers
Figure 16.14 (b) – Instrument Transformers in a Basic (Wattmeter) Circuit
Figure 16.15 – Bar-primary Current Transformer
Chapter 17 – Propulsion Systems
Figure 17.1 – Machinery Arrangement – Conventional Propeller
Figure 17.2 – Thruster Propulsion System
Figure 17.3 – Machinery Arrangement in a Thruster Propulsion System
Figure 17.4 – A Simple Ward–Leonard System
Figure 17.5– DC Motor Driven by an Alternator
Figure 17.6 – Control of Power to a Propulsion Motor
Figure 17.7 – Basic Turbo–Electric Propulsion System
Figure 17.8(a) – Basic Schematic Diagram of a Turbo–Electric Propulsion System
Figure 17.8(b) – Phasor Diagram – Overcoming No-load Losses
Figure 17.8(c) – Phasor Diagram from Bus–bar Point of View
Figure 17.8(d) – Basic Two–pole, Poly–phase Synchronous Motor
Figure 17.8(e) – Speed Torque Characteristic
Figure 17.9 – Equipment Onboard an Offshore Emergency and Supply Vessel
Figure 17.10 – Schematic Diagram of a Synchronous Motor–based Propulsion System
Figure 17.11 – Schematic Diagram of a Cycloconverter–based Propulsion System
Figure 17.12 – Frequency Change using a Cycloconverter
Figure 17.13 – A Diesel–Electric Propulsion System on a Modern Passenger Vessel
Figure 17.14 – The Propeller Drive with a Cycloconverter (SIMAR Drive Cyclo)
Figure 17.15 – Propeller Drive for an Electronic Commutator (SIMAR Drive Synchro)
Figure 17.16 – Schematic Diagram of a SIMAR Drive PWM
Figure 17.17(a) – Side View of the SSP Propulsor
Figure 17.17(b) – Rear View of the SSP Propulsor
Figure 17.17(c) – Podded Propulsion System

Figures

Chapter 17 – Propulsion Systems (Continued)
Figure 17.17(d) – Schematic Diagram of the Mermaid Pod Propulsor
Figure 17.18(a) – Shaft Motor Installed in the Shaft Line
Figure 17.18(b) – Shaft Motor Installed at the Non–drive End of a Main Engine
Figure 17.18(c) – High–speed Shaft Motor Connected via a Gearbox At the Non-drive End of a Main Engine
Figure 17.22 – Electronic Control System type TPC
Figure 17.23 – Indication of Thrust / Pitch and Backup Control
Figure 17.24 – Tunnel Thruster
Figure 17.25 – Voith–Schneider Propulsion Unit
Figure 17.26 – The Active Rudder
Figure 17.27 – Elements of a Dynamic Positioning System
Figure 17.28 – The Degrees of Freedom of a Ship
Figure 17.29 – SSBL Principles
Figure 17.30 – Taut Wire Principle
Figure 17.31 – The LBL System
Figure 17.32 – The Kamewa Water Jet – S Series
Figure 17.33 – The Kamewa Water Jet – FF Series
Figure 17.34 –The SCHOTTEL Pump–Jet
Figure 17.35 – The Double Stern Unit
Figure 17.36 – The Double Bow Unit

Chapter 18 – Steering and Stabiliser Systems
Figure 18.1 – A Steering System’s Control Console
Figure 18.2 – Non–follow up Control Diagram of a Rudder
Figure 18.3 – Two–ram Electrically–controlled, Hydraulically–operated Steering System
Figure 18.4(a) – Electronic Steering Control – Manual Mode
Figure 18.4(b) – Electronic Steering Control – Auto–pilot Mode
Figure 18.5 – Dual Cylinder – Twin Rudder
Figure 18.6 – Single Cylinder – Single Rudder
Figure 18.7 – Helm Pumps

Figures

Chapter 18 – Steering and Stabiliser Systems (Continued)
Figure 18.8 – Cylinder
Figure 18.9 – Typical System Configuration
Figure 18.10 – Three Face Panorama Rudder Angle Indicator
Figure 18.11 – Model 50 – Rudder Angle Indicators
Figure 18.12 – The Lever Follow Up Controller –Model LFU 100
Figure 18.13 – Wheel Controller – Model WFU 100
Figure 18.14 – Motor Alarm Panel – Model MCA100
Figure 18.15 – Local Control and Bridge Disconnect – Model LCB 101
Figure 18.16 – Pumpsets
Figure 18.17 – Steering Gear with Double-acting Cylinders
Figure 18.18 – 4 Keypad Fixed Control Head Controller
Figure 18.19 – AutoNav’s Steering Console
Figure 18.20 – The Distribution Unit
Figure 18.21 – The Overall Schematic Diagram
Figure 18.22 – Anschütz Auto Steering
Figure 18.23 – Steering Control System – NautoSteer
Figure 18.24 – Rudder Angle Indicator and Tiller
Figure 18.25 – FU Hand-wheel Unit
Figure 18.26 – FU Tiller
Figure 18.27 – Follow-up Amplifier
Figure 18.28 – Feedback Unit
Figure 18.29 – Solenoid Valve with On/Off Function
Figure 18.30 – NFU Hand-wheel Unit
Figure 18.31 – NFU Tiller
Figure 18.32 – Proportional Steering By Analogue Amplifier/Main Pump
Figure 18.33 – Steering Mode Selector Switch
Figure 18.34 – Rudder Position Indicators

Figures

Chapter 18 – Steering and Stabiliser Systems (Continued)
Figure 18.35 – Universal Signal Device
Figure 18.36 – Override Control
Figure 18.37 – Monitoring System
Figure 18.38 – Emergency Controls
Figure 18.39 – The Three-framed Gyroscope
Figure 18.40 – Fluid-filled Flux Gate Compass
Figure 18.41 – Rudder Position Indicators
Figure 18.42 – Two-element Synchro Chain (Initial Position of the Synchro Transmitter and Receiver)
Figure 18.43 – Torque Transmitter
Figure 18.44 – A Conceptual Diagram of a Stabiliser
Figure 18.45 – The Stabiliser and Ships on which the Gyrofin Stabiliser is fitted
Figure 18.46 – The Bridge Control Unit
Figure 18.47 – A Typical Gyrofin Installation

Chapter 19 – Deck Machinery and Cargo Equipment

Figures

Chapter 20 – Control of Air Compressors
Figure 20.1 – High Pressure Non–Oil–Free Compressor System
Figure 20.2 – Automatic Operation of a Compressor – The Basic Circuit
Figure 20.3 – Schematic Diagram of Automatic Operation
Figure 20.4 – Main Air Compressor Control Circuit
Figure 20.5 – Absorption Type Air Drier

Chapter 21 – Batteries and Battery Charging
Figure 21.1(a) – Calculation of Internal Resistance
Figure 21.1(b) – A Lead Acid Cell
Figure 21.2 – Separators
Figure 21.3 – Variation of Potential Difference on Charge and Discharge
Figure 21.4 – Voltage–Time Curves
Figure 21.5 – Variation of Capacity with Discharge Rate
Figure 21.6 – A Nickel Cadmium Cell
Figure 21.7 – A Sealed Nickel–Cadmium Cell
Figure 21.8(a) Constant Current System
Figure 21.8(b) – Constant Voltage System
Figure 21.9 – Battery Charging with DC Supply (Battery Charged in the Figure)
Figure 21.10 – Battery Charging from AC Supply
Figure 21.11 – Battery Charger and Distribution Board
Figure 21.12 – Block Diagram of the Battery Charger
Figure 21.13 – Emergency Battery Circuit
Figure 21.14 – Manual Voltage Regulator
Figure 21.15 – Automatic Voltage Regulator

Figures

Chapter 22 – Lighting Systems
Figure 22.1 – Ordinary Filament Lamp (General Lighting Service Lamp)
Figure 22.2 – Linear Tungsten–Halogen Lamp – Double–ended
Figure 22.3 – Low–pressure Mercury Fluorescent Lamp
Figure 22.4 – Typical Glow–starter Switch Circuit
Figure 22.5 –Transformer Quick–start Circuit
Figure 22.6 – High Pressure Mercury Fluorescent Lamp Circuit
Figure 22.7 – Low Pressure Sodium Vapour Lamp Circuit
Figure 22.8 – High Pressure Sodium Vapour Lamp Circuit
Figure 22.9 – Lamp Caps' Shapes
Figure 22.10 – A Basic Double Navigation Light Schematic Circuit
Figure 22.11 – Alternative Navigation Light Circuit (circuit energised)
Figure 22.12 – A Navigation Light Circuit (circuit de–energised)
Figure 22.13 – Basic Emergency Lighting Circuit
Chapter 23 – Miscellaneous Systems
Figure 23.1 – E Log I Diagram
Figure 23.2 – Sacrificial Anodes
Figure 23.2 – Sacrificial Anode System
Figure 23.4 – Impressed Current System
Figure 23.5 – Impressed Current System Circuit
Figure 23.6 – Layout of a Basic Impressed Current Cathodic Protection System
Figure 23.7(a) – Schematic Diagram of an Impressed Current Cathodic Protection System
Figure 23.7(b) – A Basic Magnetic Amplifier
Figure 23.8 – Dionic Water Purity Meter
Figure 23.9 – The Basic Salinometer
Figure 23.10 – Heater Connections for Galley Plates
Figure 23.11 – The Refrigeration Cycle
Chapter 24 – Maintenance and Troubleshooting
Figure 24.1 – A Portable Megger